



TABLE							
Unit	Dim	ASP06	ASP08	ASP12	ASP16	ASP20	ASP25
Population Equivalent		6	8	12	16	20	25
O/A Diameter	A	2000	2000	2000	2000	2000	2000
Std Inlet Invert	B	700	700	700	700	700	700
Inlet Invert to Base (mm)	C	1500	1500	1900	1900	2000	2300
Standard pumped Outlet invert (mm)	D	150	150	150	150	150	150
Outlet Invert to Base -Gravity Discharge (mm)	E	2050	2050	2450	2450	2550	2850
O/A Depth (mm)	F	2250	2250	2650	2650	2750	3150
Inlet Pipework Fitting (mm)		110	110	110	110	110	110
Plant Weight (kg)		230	230	300	300	360	440
Pumped outlet compression fitting (mm)		32	32	32	32	32	32

A	03/08/15	RP	LT	RP	Issued for information
REV	DATE	BY	CHKD	APPD	DESCRIPTION
		DO NOT SCALE IF IN DOUBT ASK ALL DIMENSIONS IN MM		TOLERANCES (unless noted otherwise) GENERAL LINEAR DIMS : +/- 5mm ANGULAR DIMENSIONS : +/- 1/2~	

THIS DRAWING IS THE PROPERTY OF PREMIERTECH AQUA LTD AND IS NOT TO BE COPIED IN PART OR WHOLE WITHOUT WRITTEN PERMISSION

Designed by		Checked by		Approved by	
rpoteaux 10/04/2015		LT 10/04/2015		RP 10/04/2015	
				Conder ASP 6-25PE Pumped Outlet	
				ASP06-08-P	

Stock Code: